



D1080BL-IR48-AF



FEATURES

NON PoC Double Reach Camera

- Provides wired remote controller for OSD control and CVBS output
- 1/3", 2.1M CMOS progressive image sensor
- Built-in DoubleReach™ Transmitter
- HD-SDI 1080p30/25, 720p30/25 or DoubleReach™ video output
- DC Iris, 2.8mm~11mm, F1.6, IR Corrective Megapixel Lens
- One-Push Auto Focus, Zoom/Focus Control (-AF Series)
- Horizontal/Vertical resolution over 1200TV lines
- Superior performance under low light environment
- (BW: 0.0005 Lux/ Color: 0.2Lux@50IRE, F1.6, 3100K, DSS off)
- 2 different settings of Exposure & Backlight for Daytime/Nighttime
- 3DNR (Noise Reduction)
- Backlight compensation of WDR/BLC/HLC
- Privacy zone masking (Color selectable)
- True Day&Night with IR cut filter removable
- Anti-Motion Blur function for fast moving object
- De-Fog function
- Smart IR function (No Saturation)
- Test Pattern output (Color bar, Stress Pattern)
- All-in-one Bracket & Housing structure supporting IP66
- Built-in IR LED : 48pcs, Max. 48m visibility

| Specifications | |
|----------------|-------------------------|
| Model Number | D1080BL-IR48-AF |
| Sensor Type | 1/3", 2.1Megapixel CMOS |

| Specifications | |
|------------------|---|
| Total Pixels | 1920(H) x 1080(V) = 2.1M pixels |
| Scanning System | Progressive Scan |
| Min Illumination | [B/W 0.0005Lux@50IRE, F1.6, 3100K, DSS(OFF), AGC(10)] |