



# DR101P-TX



## FEATURES

DoubleReach Transmitter Supporting PoC/CoC Function

- DoubleReach™ Transmitter supporting PoC/CoC function
- PoC(Power over Coax), CoC(Control over Coax)
- Camera power supply via coaxial cable (PoC)
- Camera remote control via coaxial cable (CoC)
- HD-SDI video transmission up to 1200ft based on 5C-HFBT cable
- LED indicators for Power, Video input, PoC output, RS485 output
- Additional terminal blocks for power input and RS485 output

Specifications	
Model Number	DR101P-TX
Video input standard	1CH(HD-SDI SMPTE 292M)
Resolution	SMPTE 274M(1080p30/25)
Video output standard	1CH(DoubleReach™)
Resolution	SMPTE 274M(1080p30/25)
Function	DoubleReach™ Converting
PoC	Power over Coax, Max.16W (DC24V)
CoC	Camera control data transmission, Max. 57600bps
Indication LED	Power(Red), Video In(Green), PoC Out(Red), RS485 Out(Green)
RS485 out	Terminal Block
Power input	Terminal Block (Additional Power Input DC24V)
Dimension	134(W) x 65(D) x 26(H) mm
Weight	Approx. 140g(0.3 lbs)

<b>Specifications</b>	
Operating temperature	0°C to +50°C / 20%RH to 80%RH
Power consumption	Max 3W
Approval	KC, FCC, CE, RoHS, HDcctv