



HAC-T306-FB4



FEATURES

IVMS HD 4-in-1 5MP WDR EXIR Bullet Camera

- 5Megapixel high-performance CMOS
- 4-in-1 output (TVI/CVI/AHD/CVBS)
- OSD menu, DNR, Smart IR
- 120 ft EXIR distance
- IP67 weatherproof
- DWDR

Specifications	
Model Number	HAC-T306-FB4
Image Sensor	5MP CMOS
Video Format	PAL / NTSC
Effective Pixels	2560(H)*1944(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30s to 1/50,000 s
Lens	2.8mm
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 180°, Rotation 0 - 360°
Day & Night	ICR
Video Frame Rate	2560 x 1944 @ 20fps
HD Video Output	1 BNC output (TVI/CVI/AHD/CVBS)
CVBS Output	Support
Functions	WDR, DNR, Mirror, Smart IR
White Balance	ATW / MWB

Specifications	
WDR	DWDR
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 4.3W
Weather Proof Ratings	IP67
IR Range	Up to 120 ft
Dimensions	3.41"x3.23"x8.67"
Weight	1.5lbs
Electrical Box	HTH-280ZJ-XS
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ