



HAC-T306-OD



FEATURES

IVMS HD Analog 4-in-1 5MP Exterior IR Dome Camera

- 5MP Video Output
- 4-in-1 Output (TVI/CVI/AHD/CVBS)
- OSD menu (UTC)
- 60 ft IR distance
- IP67 weatherproof
- DWDR

Specifications	
Model Number	HAC-T306-OD
Image Sensor	5MP CMOS
Video Format	PAL / NTSC
Effective Pixels	2560(H)*1944(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30s to 1/50,000 s
Lens	2.8mm
Angle Adjustment	Pan: 0 - 355°, Tilt: 0 - 75°
Day & Night	ICR
Video Frame Rate	2560 x 1944 @ 20fps
HD Video Output	1 BNC output (TVI/CVI/AHD/CVBS)
CVBS Output	Support
AGC	Support
D/N Mode	Color / BW / Auto

Specifications	
WDR	DWDR
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC±25%
Power Consumption	Max. 4.3W
Weather Proof Ratings	IP67, IK10
IR Range	Up to 60 ft
Communication	OSD (UTC Control) via DVR
Dimensions	Ø4.37"x3.24"
Weight	0.77lbs
Electrical Box	HTH-280ZJ-DM18
Wall Mount	HTH-258ZJ, HTH-272ZJ-110B
Pendant	HTH-271ZJ-110
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ