HAC-T306-VD4Z



FEATURES

IVMS HD 4-in-1 5MP Turbo HD Outdoor Motorized Vari-focal EXIR Turret Camera

- HD 5MP Video Output
- HD 4-in-1 Technology(TVI/CVI/AHD/CVBS)
- True Day/Night
- 2.7 – 13.5mm vari-focal lens
- Motorized Vari-Focal Lens
- EXIR
- OSD menu, DNR, Smart IR
- Up to 120ft IR distance
- DWDR

Specifications	
Model Number	HAC-T306-VD4Z
Image Sensor	5MP CMOS
Video Format	PAL / NTSC
Effective Pixels	2560(H)*1944(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/30 s to 1/50,000 s
Lens	2.7-13.5mm @ F1.2 Motorized, Angle of view: 95.7° – 29.1°
Day & Night	ICR
Wide dynamic range	DWDR
Synchronization	Internal synchronization
Video Frame Rate	2560*1944@20fps

Specifications	
HD Video Output	1 Analog HD output(TVI/CVI/AHD/CVBS)
CVBS Output	Support
AGC	Support
D/N Mode	Color/BW/Smart
White Balance	ATW, MWB
BLC	Support
Working Temperature / Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	Max. 9W
Weather Proof Ratings	IP67
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	5.29″ x 4.88″ x 4.39″
Weight	700 g (1.57 lbs)
Electrical Box	HTH-280ZJ-M
Wall Mount	HTH-273ZJ-130B-TRL
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ