



HAC306-MD



FEATURES

IVMS 5MP HD-TVI Exterior IR Turret Camera

- 5MP Video Output
- HDTVI Technology
- OSD menu, DNR, Smart IR
- 60 ft IR distance
- IP67 weatherproof
- Up the Coax (control over coax)
- DWDR

Specifications	
Model Number	HAC306-MD
Image Sensor	5MP CMOS
Video Format	PAL / NTSC
Effective Pixels	2560(H)*1944(V)
Min. Illumination	0.008 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30s to 1/50,000 s
Lens	3.6mm (2.8mm optional)
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day & Night	ICR
Video Frame Rate	2560*1944 @ 20fps
HD Video Output	1 HD-TVI output
CVBS Output	N/A

Specifications	
D/N Mode	Color / BW / Auto
Functions	DWDR, DNR, Mirror, Smart IR
WDR	DWDR
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC±10%
Power Consumption	Max. 3.5W
Weather Proof Ratings	IP67
IR Range	Up to 60 ft
Communication	OSD (UTC Control) via DVR
Dimensions	89.6 × 59.1 mm (3.58" × 3.25" x 2.69")
Weight	400 g (0.77 lb)
Electrical Box	HTH-280ZJ-XS
Wall Mount	HTH-272ZJ-110-TRS
Pendant Mount	HTH-271ZJ-110
Corner and Pole Mount	C:HTH-276ZJ, P:HTH-275ZJ