HAC306D-OD4ZB-28



FEATURES

IVMS HD-TVI 5MP Motorized Vari-Focal IR Dome, Exterior Grey Housing

- 5MP HD-TVI Video Output
- Grey Housing
- HDTVI Technology
- True Day/Night
- 2.8 – 12mm Motorized vari-focal lens
- OSD menu, 3D DNR, Smart IR
- Up to 120 ft IR distance
- IP67 weatherproof & IK10 Vandal Proof
- Up the Coax (control over coax)
- DWDR
- Dual Voltage 12VDC/24VAC

Specifications	
Model Number	HAC306D-OD4ZB/2.8
Image Sensor	1 / 3″ Progressive Scan CMOS
video FORMAT	PAL / NTSC
Effective Pixels	2560(H)*1944(V)
Min. Illumination	0.008 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/30s to 1/50,000s
Lens	2.8-12mm @ F1.4, Angle of view: 102° – 31°
Angle Adjustment	Pan: 0 – 355°, Tilt: 0 – 80°
Day & Night	ICR
Wide dynamic range	DWDR

Specifications	
Video Frame Rate	2560 x 1944@20fps
HD Video Output	1 HD-TVI output
CVBS Output	N/A
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/Auto
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Working Temperature / Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC, 24 VAC
Power Consumption	Max. 6W
Ratings	IP67, IK10
IR Range	Up to 120 ft
Dimensions	φ145.3 × 124.2 mm (φ5.72” × 4.89”)
Weight	880 g (3.53 lb)