



HAC314D-OD4Z



FEATURES

IVMS HD-TVI 1080P Turbo HD Outdoor Motorized Vari-focal Dome Camera

- This model has been replaced by [HAC334D-OD4Z](#)
- HD1080P Video Output
- HDTV Technology
- True Day/Night
- 2.8 - 12mm vari-focal lens
- Motorized Vari-Focal Len
- 24 pcs IR LEDs
- OSD menu, 3D DNR, Smart IR
- Up to 150ft IR distance
- Up the Coax (control over coax)

Specifications	
Model Number	HAC314D-OD4Z
Image Sensor	1 / 3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8~12mm
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps

Specifications	
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output(75Ω / BNC)
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
Privacy Mask	On/Off, maximum 2 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ; -A: 12 VDC, 24 VAC
Power Consumption	12V DC: Max. 5W ; 24V AC: Max. 8W
Ratings	IP66, IK10
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	φ145.3 × 124.2 mm (φ5.72" × 4.89"
Weight	920 g (2.03 lbs)
Wall Mount	HTH-273ZJ-140B
Pendant Mount	HTH-271ZJ-140
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ