



HAC314D-VB4Z



FEATURES

IVMS HD-TVI 1080P Turbo HD Outdoor Motorized Vari-focal EXIR Bullet Camera

- This model has been replaced by [HAC334D-VB4Z](#)
- HD1080P Video Output
- HDTV Technology
- True Day/Night
- 2.8 - 12mm vari-focal lens
- Motorized Vari-Focal Len
- 42 pcs LEDs
- OSD menu, 3D DNR, Smart IR
- Up to 150ft IR distance
- Up the Coax (control over coax)

Specifications	
Model Number	HAC314D-VB4Z
Image Sensor	1 / 3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR 0.014 Lux @ (F1.4,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8-12mm @ F1.4, Angle of view: 92° - 32°
Lens Mount	φ14
Day & Night	ICR
Wide dynamic range	N/A

Specifications	
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
CVBS Output	1Vp-p Composite Output(75Ω / BNC)
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
Privacy Mask	On/Off, maximum 2 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ; -A: 12 VDC, 24 VAC
Power Consumption	12V DC: Max. 7W ; 24V AC: Max. 10W
Weather Proof Ratings	IP66
IR Range	Up to 150 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	3.62" x 3.34" x 10.6"
Weight	700 g (1.59 lbs)
Electrical Box	HTH-260ZJ
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ