



HAC318D-VB4Z



FEATURES

IVMS 4-in-1 8MP Turbo HD Outdoor Motorized Vari-focal EXIR Bullet Camera

- 8MP Video Output
- 4-in-1 output. TVI, CVI, AHD, CVBS
- 105dB
- True Day/Night
- 2.7 - 13.5mm vari-focal lens
- Motorized Vari-Focal Len
- EXIR
- OSD menu, 3D DNR, Smart IR
- Up to 240ft IR distance
- Up the Coax (control over coax)

Specifications	
Model Number	HAC318D-VB4Z
Image Sensor	8.29MP CMOS Sensor
Video Format	95 PAL / NTSC
Effective Pixels	3840(H)*2160(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/15 s to 1/50,000 s
Lens	2.7-13.5mm @ F1.2, Angle of view: 108.1° - 45.6°
Lens Mount	φ14
Day & Night	ICR
Wide dynamic range	105dB WDR
Synchronization	Internal synchronization

Specifications	
Video Frame Rate	TVI: 8MP @ 15FPS, 5MP @ 20FPS, 4MP @ 30FPS CVI: 8MP @ 15FPS, AHD: 5MP @ 20FPS
HD Video Output	1 Analog HD output
CVBS	No
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
BLC	Support
S/N Ratio	More than 52db
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12VDC, 24VAC
Power Consumption	Max. 10.8W
Weather Proof Ratings	IP67
IR Range	Up to 240 ft
Communication	Up the coax(need UTC controller) Protocol: Coaxitron-C(Coaxitron)
Dimensions	3.33" x 3.62" x 10"
Weight	1.53 lbs
Electrical Box	HTH-280ZJ-S
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ