

HAC324F-FD4



FEATURES

IVMS 2MP EXIR Turret Camera

- 2MP Video Output
- HDTVI
- OSD menu, DNR
- 120 ft IR distance
- IP66 weatherproof
- Up the Coax (control over coax)
- DWDR

Specifications	
Model Number	HAC324F-FD4
Image Sensor	2MP CMOS Sensor
Video Format	PAL / NTSC
Effective Pixels	1928(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25s to 1/50,000 s
Lens	3.6 mm(2.8, 6mm optional)
Angle Adjustment	Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360°
Day & Night	ICR
Video Frame Rate	1080p@ 30fps
HD Video Output	HDTVI
D/N Mode	Color / BW / Smart
Function	DWDR, DNR, Mirror, Smart IR

Specifications	
WDR	DWDR
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 5W
Weather Proof Ratings	IP66
IR Range	Up to 120 ft
Communication	OSD (UTC Control) via DVR
Dimensions	Ø4.33"x3.67"
Weight	0.77lbs
Electrical Box	HTH-285ZJ-M(B), HTH-280ZJ-M
Wall Mount	HTH-273ZJ-130B-TRL
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ
Ceiling Mount	C:HTH-271ZJ-130-TRL