HAC334-OD



FEATURES

IVMS HD-TVI 2MP Exterior IR Dome Camera

- 2MP Video Output
- HD-TVI Technology
- OSD menu, DNR
- 65 fts IR distance
- IP66 weatherproof
- Up the Coax (control over coax)
- True WDR

Specifications	
Model Number	HAC334-OD
Image Sensor	2MP CMOS Sensor
Video Format	PAL / NTSC
Effective Pixels	1928(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/25s to 1/50,000 s
Lens	3.6mm (6mm optional), Angle of View: 80.9°(3.6mm), 54.3°(6mm)
Angle Adjustment	Pan: 0 – 360°, Tilt: 0 – 80°
Day & Night	ICR
Video Frame Rate	1080p @ 30fps
HD Video Output	1 HD-TVI output up to 1200ft with RG59U 95%
CVBS Output	N/A

Specifications	
AGC	support
D/N Mode	Color / BW / Smart
WDR	120dB True WDR
Working Temperature / Humidity	-40 °C – 60 °C (-40 °F – 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC±15%
Power Consumption	Max. 5W
Weather Proof Ratings	IP66, IK10
IR Range	Up to 65 ft
Communication	OSD (UTC Control) via DVR
Dimensions	θ4.37″x3.24″
Weight	0.77lbs
Electrical Box	HTH-280ZJ-DM18
Wall Mount	HTH-258ZJ, HTH-272ZJ-110B
Pendant	HTH-271ZJ-110
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ