



HAC334-VD4Z



FEATURES

IVMS HD-TVI 1080P Turbo HD Outdoor Motorized Vari-focal Turret Camera

- HD1080P Video Output
- Adopt HDTVI Technology 4 in 1
- True Day/Night
- 2.8 - 12mm vari-focal lens
- Motorized Vari-Focal Len
- OSD menu, 3D DNR, Smart IR
- Up to 150ft IR distance
- Up the Coax(via coaxial cable)

Specifications	
Model Number	HAC334-VD4Z
Image Sensor	2MP CMOS Sensor
Video Format	PAL / NTSC
Effective Pixels	1928(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8-12mm
Day & Night	ICR
Synchronization	Internal synchronization
Video Frame Rate	1080p@25fps/1080p@30fps
HD Video Output	1 Analog HD output
Wide Dynamic Range	120dB True WDR

Specifications	
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
Camera ID	On/off (15 characters, position programmable)
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
Privacy Mask	On/Off, maximum 2 zones
Motion Detection	On/Off, maximum 4 zones
BLC	Support
Anti-flicker	On/off
Language	English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC
Power Consumption	12V DC: Max. 7W
Weather Proof Ratings	IP66
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	Φ5.29" x 4.88" x 4.39"
Weight	1.57 lb
Electrical Box	HTH-280ZJ-M
Wall Mount	HTH-273ZJ-130B-TRL
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ