



HAC334D-OD4ZB



FEATURES

IVMS HD-TVI 1080P Turbo HD Outdoor Motorized Vari-focal Dome Camera

- Grey Housing
- HD1080P Video Output
- HDTVI Technology
- True WDR
- True Day/Night
- 2.8 - 12mm vari-focal lens
- Manually Adjustable Zoom and Focus
- Motorized Vari-Focal Len
- 24 pcs IR LEDs
- OSD menu, 3D DNR, Smart IR
- Up to 120ft IR distance
- Up the Coax (control over coax)

Specifications	
Model Number	HAC334D-OD4ZB
Image Sensor	2MP CMOS Sensor
Video Format	PAL / NTSC
Effective Pixels	1928(H)*1088(V)
Min. Illumination	0.01 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8~12mm
Day & Night	ICR

Specifications	
Synchronization	Internal synchronization
Video Frame Rate	1080p@30fps
HD Video Output	1 Analog HD output
Wide Dynamic Range	True WDR
S / N Ratio	More than 52dB
Scene	Indoor, Outdoor, Indoor1, LOW-LIGHT
CVBS	Yes
AGC	Support
D/N Mode	Color/BW/EXT
White Balance	ATW, AWC-SET, Indoor, Outdoor, Manua
BLC	Support
Function	Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC ;24 VAC
Power Consumption	12V DC: Max. 4.5W 24V AC: Max. 6.5W
Ratings	IP66, IK10
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	φ145.3 × 124.2 mm (φ5.72" × 4.89")
Weight	3.53 lbs
Wall Mount	HTH-273ZJ-140B
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ
Pendant Mount	HTH-271ZJ-140