

HAC336D-OD4Z



FEATURES

5 MP Vandal-proof Motorized Varifocal Dome Camera

- 5 MP high performance CMOS
- 2560 × 1944 resolution
- 2.7 mm to 13.5 mm motorized varifocal lens
- 40m IR range
- OSD menu, 2D DNR, DWDR
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67, IK10
- Up the coax (UTC-C)

Image Sensor	5 MP CMOS
Signal System	PAL/NTSC
Resolution	2560 (H) × 1944 (V)
Min. Illumination	Color: 0.01 Lux@(F1.2, AGC ON), 0 Lux with IR
Frame Rate	TVI: 5 M @ 20 fps, 4 M @ 30 fps, 4 M @ 25 fps, 1080p @ 30 fps, 1080p @ 25 fps AHD: 5 M @ 20 fps, 4 M @ 30 fps, 4 M @ 25 fps CVI: 4 M @ 30 fps, 4 M @ 25 fps CVBS: PAL/NTSC
Shutter Time	1/30 s to 1/50,000 s
Lens	2.7 mm to 13.5 mm motorized varifocal lens
Horizontal Field of View	95° to 26°
Lens Mount	Φ 14
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 355°; Tilt: 0° to 75°; Rotate: 0° to 355°
WDR (Wide Dynamic Range)	DWDR
Day/Night Mode	Auto/Color/BW (Black and White)
Image Mode	STD/HIGH-SAT

White Balance	Auto/Manual
BLC (Backlight Compensation)	Yes
2D DNR	YES
Language	English
Functions	Brightness, Sharpness, Smart IR
Video Output	1 BNC Output
Switch Button	TVI/AHD/CVI/CVBS
Switch Button	TVI/AHD/CVI/CVBS
IR Range	130ft
Power Supply	12 VDC±15%, 24 VAC±15%
Power Consumption	Max. 5.9 W
Protection Level	IP67, IK10
Material	Metal
Communication	Up the coax, Protocol: UTC-C (TVI output)
Dimensions	Φ 145.2 mm × 111.3 mm (Φ 5.69" × 4.37")
Weight	Approx. 640 g (1.85 lb.)
Electrical Box	HTH-280ZJ-DM21A
Wall Mount	HTH-273ZJ-140-DM45
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ
Pendant Mount	HTH-271ZJ-140-DM45