

HAC344-FB4



FEATURES

2 MP Ultra Low-Light EXIR Bullet Camera

- 2.0 megapixel high-performance CMOS
- HD analog output, up to 1080p resolution
- 2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens
- True Day/Night
- 130 dB true WDR
- OSD menu, DNR, Smart IR
- EXIR 2.0, up to 600 m IR distance
- IP67
- Up the Coax (UTC-C)

Image Sensor	2.0 megapixel progressive scan CMOS
Frame Rate	PAL: 1080p@25fps, 1080p@30fps NTSC: 1080p@25fps, 1080p@30fps
Resolution	1920 (H) × 1080 (V)
Min. illumination	Color: 0.003 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30 s to 1/50,000 s
Slow Shutter	Max. 16 times
Lens	2.8 mm, 3.6 mm, 6 mm, 8 mm, 12 mm fixed focal lens
Horizontal Field of View	104° (2.8 mm), 79.1° (3.6 mm), 50.2° (6 mm), 38.7° (8 mm)
Lens Mount	M12
Day & Night	IR cut filter
Angle Adjustment	Pan: 0° to 360°, Tilt: 0° to 180°, Rotate: 0° to 360°
Synchronization	Internal synchronization
WDR (Wide Dynamic Range)	> 130 dB
AGC	Support
Day/Night Mode	Auto/Color/BW (Black and White)
White Balance	ATW/ MANUAL
Privacy Mask	ON/OFF, 4 programmable privacy masks
Motion Detection	4 programmable motion areas
Backlight Compensation	WDR/BLC/HLC/OFF
3D DNR (Digital Noise Reduction)	On
Functions	Brightness, Sharpness, Mirror, Smart IR
Video Output	1 HD analog output
Operating Conditions	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensation)

Power Supply	12 VDC±25%
Power Consumption	Max. 3.4 W
Ingress Protection	IP67
Material	Metal
IR Range	Up to 60 m
Dimensions	88.8 mm × 81.6 mm × 227 mm (3.5" × 3.2" × 8.94")
Weight	Approx. 680 g (1.5 lb.)
Junction Box	
HTH-280ZJ-XS	