



HAC346-OD



FEATURES

IVMS HD-TVI 5MP Exterior IR Dome Camera OSD menu, 3D DNR, 130 dB true WDR 5MP Video Output 4 in 1 Technology, TVI, CVI, AHD, CVBS OSD menu, DNR EXIR 2.0, smart IR, up to 30 m IR distance IP67, IK10 Up the Coax (control over coax)

Dimensions Φ 111 mm $\times$ 82.4 mm (Φ 4.4" $\times$ 3.2")

Specifications	
Image Sensor	5MP CMOS
Resolution	2560(H)*1944(V)
Min. Illumination	0.003 Lux@(F1.2, AGC ON), 0 Lux with IR
Shutter Time	1/30 s to 1/50,000 s
Lens	2.8 mm fixed lens
Angle Adjustment	Pan: 0° to 355°, Tilt: 0° to 75°, Rotate: 0° to 355°
Day & Night	IR Cut Filter
Video Frame Rate	TVI: 2 MP@25fps, 2 MP@30fps, 4 MP@25fps, 4 MP@30fps, 5 MP@20fps AHD: 4 MP@25fps, 4 MP@30fps, 5 MP@20fps CVI: 4 MP@25fps, 4 MP@30fps CVBS: PAL, NTSC
AGC	Supported
Day/Night Mode	Auto/Color/Black and White
WDR	$\geq$ 130 dB
Working Temperature / Humidity	-40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensing)
Power Supply	12 VDC $\pm$ 25%
Power Consumption	Max. 5.8W
Weather Proof Ratings	IP67, IK10

Specifications	
IR Range	Up to 30 m
Communication	OSD (UTC Control) via DVR
Weight	Approx.500 g (1.10 lb.)
Electrical Box	HTH-280ZJ-DM18
Wall Mount	HTH-258ZJ, HTH-272ZJ-110B
Pendant	HTH-271ZJ-110
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ