



HAC354-ID3



FEATURES

IVMS HD-TVI 2MP Turbo HD Indoor Motorized Vari-focal Dome Camera

- 1080P Video Output
- HDTVI Technology
- True Day/Night
- 2.8 - 12mm vari-focal lens
- Motorized Vari-Focal Lens
- OSD menu, 3D DNR, Smart IR
- Up to 90ft IR distance
- Support Dual output HDTVI and CVBS

Specifications	
Model Number	HAC354-ID3
Image Sensor	2MP Progressive Scan CMOS
Video Format	PAL / NTSC
Effective Pixels	1920(H)*1080(V)
Min. Illumination	0.003 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/25 s to 1/50,000 s
Lens	2.8-12mm @ F1.2 Motorized, Angle of view: 98° - 32.1°
Day & Night	ICR
Wide dynamic range	120dB True WDR
Synchronization	Internal synchronization
Video Frame Rate	1920*1080@30fps
HD Video Output	1 Analog HD output

Specifications	
CVBS Output	1 Analog output, when enabled will disable WDR
S / N Ratio	More than 62dB
AGC	Support
D/N Mode	Color/BW/Smart
White Balance	ATW, MWB
BLC	Support
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC, 24VAC
Power Consumption	12 VDC, 24VAC Max: 6W
IR Range	Up to 90 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	5.35" x 4.01"
Weight	1.76 lbs
Recess Mount	HTH-229ZJ
Wall Mount	HTH-273ZJ-130B
Pole,Corner	P:HTH-275ZJ, HTH-271ZJ-135 C:HTH-276ZJ