

# HAC354D-VB4Z



## FEATURES

IVMS HD-TVI 1080P Turbo HD Outdoor Motorized Vari-focal EXIR Bullet Camera

- HD1080P Video Output
- HDTV Technology
- 120dB True WDR
- True Day/Night
- 2.8 - 12mm vari-focal lens
- Motorized Vari-Focal Len
- Dual Video Output. HDTV and CVBS
- OSD menu, 3D DNR, Smart IR
- Up to 120ft IR distance
- Up the Coax (control over coax)

| Specifications     |  |
|--------------------|--|
| Model Number       | HAC354D-VB4Z                                   |
| Image Sensor       | 2MP Progressive CMOS Scan Sensor               |
| Video Format       | 95 PAL / NTSC                                  |
| Effective Pixels   | 1920(H)*1080(V)                                |
| Min. Illumination  | 0.003 Lux @ (F1.2,AGC ON),0 Lux with IR        |
| Shutter speed      | 1/25 s to 1/50,000 s                           |
| Lens               | 2.8-12mm @ F1.2, Angle of view: 98° - 32.1°    |
| Lens Mount         | φ14  |
| Day & Night        | IR Cut Filter                                  |
| Wide dynamic range | 120dB True WDR                                 |
| Synchronization    | Internal synchronization                       |
| Video Frame Rate   | 1080p@30fps                                    |
| HD Video Output    | 1 HD-TVI output                                |
| CVBS               | 1 Analog output. When enabled will disable WDR |
| Scene              | Indoor, Outdoor, Indoor1, LOW-LIGHT            |

| <b>Specifications</b>          |  |
|--------------------------------|--|
| AGC                            | Support  |
| D/N Mode                       | Color/BW/EXT   |
| White Balance                  | ATW, AWC-SET, Indoor, Outdoor, Manua                                   |
| BLC                            | Support  |
| S/N Ratio                      | More than 52db   |
| Working Temperature / Humidity | -40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing) |
| Power Supply                   | 12 VDC ; -A: 12 VDC, 24 VAC  |
| Power Consumption              | 12V DC: Max. 7W ; 24V AC: Max. 7.5W                                    |
| Weather Proof Ratings          | IP67   |
| IR Range                       | Up to 120 ft   |
| Communication                  | Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)          |
| Dimensions                     | 3.62" x 3.36" x 10.61"   |
| Weight                         | 1.54 lbs   |
| Electrical Box                 | HTH-280ZJ-S  |
| Pole Mount                     | HTH-275ZJ  |
| Corner Mount                   | HTH-276ZJ  |