



HACC-KIS603-P



FEATURES

Door Station System w/ Monitor

- Standard PoE
- 2 MP HD camera
- Noise suppression and echo cancellation
- Low illumination
- Access control functions
- Tamper-proof
- Configuration remotely via Web (doorbell camera only)
- 2.4 GHz Wi-Fi

| Specifications | |
|----------------------------|---|
| Flash | 32M, 16M |
| RAM | 256M |
| Operation Method | Single Button |
| Operating System | Embedded Linux OS |
| Camera | 2MP HD Camera |
| Night Vision | Low Illumination IR Supplement Mode: 3m |
| BLC | Support |
| DNR | Support |
| WDR | True WDR |
| Field of View | Horizontal: 129 °, Vertical: 75 ° |
| Video Compression Standard | H.264 |
| Stream | Main stream: 1080p@30fps, 720p@25fps Sub stream: D1@25fps |

| Specifications | |
|----------------------------|---|
| Resolution | Main stream: 1920 × 1080p, 720p Sub stream: 704 × 576 |
| Motion Detection | Support |
| Anti-Flicker Frequency | 50 Hz, 60 Hz |
| Audio Intercom | Two-way Audio Communication |
| Audio Input | Built-in omnidirectional microphone |
| Audio Output | Built-in Loudspeaker |
| Audio Compression Standard | G.711 U |
| Audio Compression Rate | 64Kbps |
| Audio Quality | Noise Suppression and Echo Cancellation |
| Wired Network | 10/100M Ethernet |
| Network Protocol | TCP/IP, RTSP |
| Reading Frequency | 13.56 MHz |
| Card Type | Mifare Card |
| Relay | 1 |
| RS-485 | 1 |
| Wi-Fi | 2.4 GHz |
| Debugging Port | 1 |
| Alarm Input | 4 |
| Grounding | 1 |
| TAMPER Switch | 1 |
| Physical Button | 1 |
| Protection Level | IP65 |
| Indicator | 2 |
| Power Supply | IEEE802.3af, standard PoE 12 VDC |
| Power Consumption | ≤ 10 W |
| Heating Module | Support |
| Working Temperature | -40 °C to +53 °C (-40 °F to +127.4 °F) |
| Working Humidity | 10% to 95% |
| Installation | Surface Mounting |