

HACC-KIS603-P



FEATURES

Single-Button Villa Door Station

- Standard PoE
- 2 MP HD camera
- Noise suppression and echo cancellation
- Low illumination
- Access control functions
- Tamper-proof
- Configuration remotely via Web
- 2.4 GHz Wi-Fi

Specifications	
Flash	32M, 16M
RAM	256M
Operation Method	Single Button
Operating System	Embedded Linux OS
Camera	2MP HD Camera
Night Vision	Low Illumination IR Supplement Mode: 3m
BLC	Support
DNR	Support
WDR	True WDR
Field of View	Horizontal: 129 °, Vertical: 75 °
Video Compression Standard	H.264
Stream	Main stream: 1080p@30fps, 720p@25fps Sub stream: D1@25fps

Specifications	
Resolution	Main stream: 1920 × 1080p, 720p Sub stream: 704 × 576
Motion Detection	Support
Anti-Flicker Frequency	50 Hz, 60 Hz
Audio Intercom	Two-way Audio Communication
Audio Input	Built-in omnidirectional microphone
Audio Output	Built-in Loudspeaker
Audio Compression Standard	G.711 U
Audio Compression Rate	64Kbps
Audio Quality	Noise Suppression and Echo Cancellation
Wired Network	10/100M Ethernet
Network Protocol	TCP/IP, RTSP
Reading Frequency	13.56 MHz
Card Type	Mifare Card
Relay	1
RS-485	1
Wi-Fi	2.4 GHz
Debugging Port	1
TF Card	Max to 128 G
Alarm Input	4
Grounding	1
TAMPER Switch	1
Physical Button	1
Protection Level	IP65
Indicator	2
Power Supply	IEEE802.3af, standard PoE 12 VDC
Power Consumption	□ 10 W
Heating Module	Support
Working Temperature	-40 °C to +53 °C (-40 °F to +127.4 °F)
Working Humidity	10% to 95%
Installation	Surface Mounting