



# HACC-KIS701



## FEATURES

### Two-Wire Video Intercom Bundle Door Station

- Video intercom Function
- Low Illumination 2MP HD Colorful 155 Fisheye Camera
- Tampering Alarm and Door Magnetic Alarm Supported
- Supports Surface Mounting and Flush Mounting

### Indoor Station

- Hands-free audiovisual communication with the door station and the master station in the intercom system
- Supports monitoring door stations and external cameras
- Noise suppression and echo cancellation
- Community notice supported

### Video/Audio Distributor

- Nine two-wire interface to support nine two-wire indoor stations
- One 10/100M self-adaptive network interface to support external switch
- 24 VDC power supply and communications between door stations and indoor station

Specifications	Door Station
<b>System Parameters</b>	
Processor	High-Performance Embedded SOC Processor
Operating System	Embedded Linux Operating System
<b>Video Parameters</b>	
Camera	CMOS Low Illumination 2MP HD Colorful 155° Fisheye Camera
Video Compression Standard	H.264
Resolution	1920x1080
Video Frame Rate	NTSC: 30fps PAL: 25fps
<b>Audio Parameters</b>	
Audio Input	Built-in Omnidirectional Microphone

<b>Specifications</b>	<b>Door Station</b>
Audio Output	Built-in Loudspeaker
Audio Compression Standard	G.711 U
Audio Compression Rate	64Kbps
Audio Quality	Noise Supresion and Echo Cancellation
<b>Access Control Parameters</b>	
Exit Button	Exit Button for Opening the Door
Door Magnetic Detection	Detects Door Magnetic Status
<b>Light Supplement</b>	
Light Supplement Mode	IR Supplement
<b>Network Parameters</b>	
Ethernet	10/100 Mbps Self-Adaptive Ethernet
Network Protocol	TCP/IP, RTSP
<b>Alarm Parameters</b>	
Alarm Input	Door Magnetic Alarm, Tampering Alarm
<b>Device Interfaces</b>	
Network Interface	Two-Wire Interface
RS-485	1 RS-485 Half-Duplex Port
I/O Input	2
I/O Output	1-ch 12 VDC Output
<b>General</b>	
Material	Stainless Steel
Power Supply	Included
Power Consumption	≤12 W
Working Temperature	-30 °C to +60 °C (-22 °F to 140 °F)
Working Humidity	10% to 90%
IP Protection Level	IP 65
Dimensions (L x W x H)	169 mm x 110 mm x 44 mm (6.65" x 4.33" x 1.73")
<b>Speceficaiton</b>	<b>Indoor Station</b>
<b>System Parameter</b>	
Processor	High-Performance Embedded SOC Processor
<b>Display Parameters</b>	
Display Screen	7-inch Colorful TFT LCD
Display Resolution	1024x600
Operation Method	Capacative Touch Screen, Touch Button
Operation Interface	Flattened UI Operation Interface
<b>Video Parameter</b>	
Video Compression Standard	H.264
<b>Audio Parameters</b>	
Audio Input	Built-in Omnidirectional Microphone
Audio Output	Built-in Loudspeaker
Audio Quality	Noise Suppression and Echo Cancellation

<b>Specifications</b>	<b>Door Station</b>
<b>Device Interfaces</b>	
Network Interface	Two-Wire Interface
RS-485 Interface	1, Half-duplex interface
Alarm Output	1
<b>General</b>	
Power Supply	Included
Power Consumption	Max 10 W.
Working Temperature	-10 ° C to +55 ° C (14 ° F to 131 ° F)
Working Humidity	10% to 90%
Installation	Wall Mounting
Dimensions	196 mm × 133 mm × 25.75 mm (7.72" × 5.24" × 1.01")
<b>Specifications</b>	
<b>Video/Audio Distributor</b>	
Interface Number	1, 10/100M Interface
Interface Type	9-ch 2-wire Interface
Power Supply	24 VDC
Power Consumption	60W
Working Temperature	-10 °C to 55 °C
Working Humidity	10% to 90%, No Condensing
Dimensions	112.2 mm x 111 mm x 66 mm (4.42" × 4.37" × 2.60")