



HAP313-OD



FEATURES

1/3'' High Performance CMOS HD-TVI 1080P Outdoor 30x PTZ Dome Camera

- 1/3'' high performance CMOS, up to 1920×1280 resolution
- $\pm 0.1^\circ$ Preset Accuracy
- Self-adaptive to HIKVISION, Pelco-P/D protocol
- 3D intelligent positioning function
- Power-off memory function: restore PTZ & Lens status after reboot
- Built-in temperature sensor, with display of internal temperature
- Lightning protection, surge protection and voltage transient protection
- IP66 standard (outdoor dome)
- RS-485 communication diagnosis
- Scheduled PTZ movement
- UTC (Up the Coax) function
- 360° endless pan range and -5°-90° tilt range
- 24VAC

Specifications	
Model Number	HAP313-OD
Image Sensor	1/3'' CMOS
Max. Image Resolution	1920×1080
Frame Rate	60Hz:30fps(1280×1080)
Min. Illumination	Color: 0.02Lux@(F1.6,AGC ON), B/W: 0.002Lux@(F1.6,AGC ON)
HD Video Output	1 HD-TVI out (up to 1200ft with RG59U 95%), 1 Analog out
White Balance	Auto / Manual / ATW / Indoor / Outdoor

Specifications	
AGC	Auto / Manual
S / N Ratio	≥ 50dB
3D DNR	Support
Backlight Compensation	Support
WDR	True WDR
Shutter Speed	NTSC: 1-1/10,000s
Day & Night	IR Cut Filter
Optical Zoom	30X
Digital Zoom	16x
Alarm I/O	2/1
Focus Model	Auto / Semiautomatic / Manual
Focal Length	4-120mm, 30X
Zoom Speed	Approx.3.0s(Optical Wide-Tele)
Angle of View	58-21.7 degree(Wide-Tele)
Min. Working Distance	10-1500mm (Wide-Tele)
Aperture	F1.6-F4.4
Pan Range	360° endless
Pan Speed	Pan Manual Speed: 0.1°-250°/s, Pan Preset Speed: 300°/s
Tilt Range	-5°-90° (Auto Flip)
Tilt Speed	Tilt Manual Speed: 0.1°-150°/s,
Tilt Speed	Tilt Manual Speed: 0.1°-150°/s, Tilt Preset Speed: 200°/s
Proportional Zoom	Rotation speed can be adjusted automatically according to zoom multiples
Number of Preset	256
Patrol	8 patrols, up to 32 presets per patrol
Pattern	4 patterns, with the total recording time not less than 10 minutes
Power-off Memory	Support
Park Action	Preset / Patrol / Pattern / Pan scan / Tilt scan / Frame Scan / Random scan / Panorama scan
PTZ Position Display	On / Off
Preset Freezing	Support
Scheduled Task	Preset / Patrol / Pattern / Pan scan / Tilt scan / Frame Scan / Random scan / Panorama scan
Monitor Output	1 turbo HD1080p output 1.0V[p-p] / 75Ω, NTSC (or PAL) composite, BNC
RS-485 Interface	Half-duplex mode Self-adaptive HIKVISION, Pelco-P, Pelco-D protocol
RS-485 communication diagnosis	Pelco-P, Pelco-D, OSD (UTC control) via DVR
Menu Language	English, Chinese
Power	24VAC Outdoor dome: Max. 20W (Heater On), Max. 12W(Heater Off) Indoor dome: Max.12W

Specifications	
Operating Temperature / Humidity	-30 °C-65°C(-22°F-149°F)(outdoor dome) / -10°C-50°C(14°F-122°F)(indoor dome) 90% or less
Protection Level	IP66 standard (outdoor dome) TVS 4,000V lightning protection, surge protection and voltage transient protection
Impact Protection	IK10
Dimension	φ8.66"×12.0"
Weight	6.61 Lbs
Wall, Pendant Mounting	W: HTH-602-ZJ, P: HTH-661-ZJ, HTH-662-ZJ
Pole, Corner Moutning	P: HTH-602ZJ-POLE, C: HTH-602ZJ-CORNER