



HAR304-16



MB-149 效果图

FEATURES

Twin Turbo HD 1080P 16 Channel DVR

- H.264 & Dual-stream video compression
- Support both HD-TVI and analog cameras with adaptive access
- Support 2 IP Cameras, up to 2 MP
- Alarm I/O, 16/4
- Full Channel@720P resolution real-time recording
- HDMI and VGA output at up to 1920 x 1080P resolution
- Long transmission distance over coax cable
- Support up to 16 ch synchronous playback

Specifications	
Model Number	HAR304-16
Video compression	H.264
Analog and HD-TVI video input	16 ch, BNC interface (1.0Vp-p, 75Ω)
Supported camera types	720P25, 720P30, 720P50, 720P60, 1080P25, 1080P30, CVBS
Audio compression	G.711u
Audio input / Two-way audio in	1 ch, RCA (2.0 Vp-p, 1 KΩ)
Alarm I/O	16/4
Video Output	1 HDMI, 1 VGA
HDMI / VGA output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz

Specifications	
Encoding resolution	Main stream: 1080P(non-real-time) / 720P / VGA / WD1 / 4CIF / CIF; Sub-stream: WD1(non-real-time) / 4CIF(non-real-time) / CIF / QCIF / QVGA
Frame Rate	Main stream: 1/16 fps ~ Real time frame rate Sub-stream: 1/16 fps ~ Real time frame rate
Video bitrate	32 Kbps-6 Mbps
Audio output	1 ch, RCA (Linear, 1KΩ)
Audio bitrate	64 Kbps
Dual-stream	Support
Stream type	Video, Video & Audio
Synchronous playback	16 ch
Playback resolution	1080P / 720P / VGA / WD1 / 4CIF / CIF / QVGA / QCIF
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
SATA	2 SATA interfaces
Capacity	Up to 6 TB capacity for each disk
Network interface	1; 10M / 100M / 1000M self-adaptive Ethernet interface
Serial interface	1; standard RS-485 serial interface, half-duplex
USB port	2 × USB2.0
Power suppl	12V DC
Consumption (without hard disks)	≤ 20W
Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Working humidity	10% ~ 90%
Chassis	380mm 1U chassis
Dimensions (W × D × H)	380 × 290 × 48mm (15.0 × 11.4 × 1.9 inch)
Weight (without hard disks)	≤ 2Kg (4.4lb)