



HARA05-16



FEATURES

16 Channel, 2MP TVI & Analog + Up to 32 Ch. IP Hybrid DVR

- 260 Mbps bit rate input max for IP cameras
- H.264+ video compression
- 1080p resolution real-time recording
- Third-party network cameras supported
- Up to 6 Megapixels resolution recording
- HDMI and VGA output up to 1080P
- 16 Ch. synchronous playback
- Dual Gigabit network interfaces
- ONVIF compliant

Specifications	
Model Number	HARA05-16
Video Compression	H.264 / H.264+
IP Video Input	Up to 32 Ch. (Up to 6MP)
Video Output	1 HDMI, 1 VGA, 1 BNC
Analog Video Input	16
Incoming Bandwidth	260Mbps
Audio Input/output	16/2
Two-way Audio	1/1
Real-time recording resolution	30fps @ Up to 6 Megapixels
HDMI Output Resolution	1080P 60Hz
VGA Output Resolution	1080P, 60Hz
Synchronous Playback	16 Ch. @ 1080p

Specifications	
Alarm Input/ Output	16/4
Network Interface	2 RJ45 10M/100M/1000M adaptive Ethernet Interface
RAID	0, 1, 5, 10
HDD Interface	8 SATA interfaces(up to 6TB each)
eSATA	1 eSATA
Serial Interface	RS-232, RS-485, Keyboard
USB interface	3 x USB 2.0
Chassis	19-inch rack-mounted 2U
Power Supply	100~240VAC, 65W
Power Consumption	Max 65W. (without HDD)
Dimensions	17.5"W x 18.5"D x 3.5"H
Weight	17.64 lbs (without hard disk)