



HARA26-32



FEATURES

HD-TVI 8MP 64 Channel Hybrid DVR

- H.265 & Dual-stream video compression
- Support HD-TVI/analog/AHD/HDCVI/IP camera hybrid
- Support 32 IP Cameras, up to 12 MP
- Disable TVI in order to add more IP up to 64-ch
- HDMI output up to 4K resolution
- Connectable to the Coaxitron camera/dome with long transmission distance
- Support up to 16 Ch. synchronous playback

Specifications	
Model Number	HARA26-32
Video compression	H.265+ / H.265 / H.264+ / H.264
Video Input	HDTVI up to 8MP, AHD up to 5MP, HDCVI up to 4MP, CVBS
IP Video Input	32-ch (up to 64-ch), up to 12MP resolution.
Audio compression	G.711u
Audio Input	16 Ch. input
HDMI1 / VGA output	1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
HDMI2 output	4K (3840 x 2160)30Hz / 2K (2560 x 1440)60Hz / 1920 × 1080 / 60 Hz, 1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
Encoding resolution	Up to 8MP
Frame rate	Main stream: 8MP@ 8fps; 5MP@12fps; 4MP@15fps; 3MP@18fps; 1080p/720p/WD1/4CIF/VGA/CIF@30fps Sub-stream: WD1/4CIF/CIF@30fps

Specifications	
Video bitrate	32 Kbps to 10 Mbps
Audio output	2 Ch., RCA (Linear, 1KΩ)
Audio bitrate	64 Kbps
Alarm I/O	16/8
Dual-stream	Support
Stream type	Video & Audio
Synchronous playback	16 Ch. @ 1080p
Remote connections	128
HDD Type	8 SATA interfaces for 8 HDDs; 1 eSATA interface
Network protocols	TCP/IP, PPPoE, DHCP, DNS, DDNS, NTP, SADP, SMTP, SNMP, NFS, iSCSI, UPnP™, HTTPS
Capacity	Up to 10 TB capacity for each disk
Network interface	2; 10M / 100M / 1000M self-adaptive Ethernet interface
Serial interface	RS-232, RS-485, Keyboard
USB Interface	2 × USB2.0, 1 x USB3.0
Power	100 ~ 240VAC, Max. 74W
Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Working humidity	10% ~ 90%
Dimensions (W × D × H)	17.5"W × 18.5"D × 3.5"H
Weight (Without hard disks)	22 lbs