



HCD-08MAH



FEATURES

8-inch Security Surveillance Metal Case LCD Monitor with 2D Filter, 1 Composite Video in/out, S-Video, VGA, View angle: 60/65/70/70 (L/R/T/B), On-Screen Display Control (OSD), Pixel Pitch 0.213mm x 0.213mm, Number of pixels: 800×600, 16.2 million color, Brightness: 250cd/m2, response time 30ms, Power AC 100V ~ 240V

- Digital/Analog Input with DVI-I and D-sub
- Built-in 3D Filter
- NTSC/PAL Auto Scan
- 140-Degree Viewing Angles
- Y/C and Composite Video Input
- Looping Device
- Resolution Up to 1366×768 and 2500:1 Contrast Ratio (HCD-26MAH)
- Built-in Audio
- Built-in Multi-Language OSD Menu

Specifications	
Model Number	HCD-08MAH
Panel Type	8" TFT color LCD
Built in Filter Type	2D
Viewable ize mm	N/A
Dot Pitch mm	0.213 x 0.213
Viewing Angle L/R/T/B	60/65/70/70
Contrast Ratio	500:1
Brightness	250 cd/m2

Specifications	
Resolution	800×600
Display Color	16.2M+
Response Time	30ms
Power Input	100~240VA
Power Consumption	60W (Max)
Dimension WxHxD mm	8.46×7.36×2.95
Weight (lbs)	5.1
Wall Mount	VESA 75x75mm
Input Signal PC	Connector: BNC + VGA
Input Signal	NTSC/ PAL dual Scan composite video Connector: Level: 1.0Vp-p/ 75 ohm
Input Connectors	1BNC for CVBS input, 1 mini-din 4pin for S-video
Audio	N/A
Plug & Play	DDC2B
Power Management	User's manual, power code, audio cable, DVI to D-SUB cable
Accessory	FCC, CE, UL, TCO
Regulation	