



HCD-15AH



FEATURES

15-inch Advanced Security Surveillance TFT LCD Monitor with 3D Comb filter, 3D noise filter, 1 Composite Video in/out, 1 S-Video in/out, VGA in, Audio in/out, View angle: 70/70/65/60 (L/R/T/B), On-Screen Display Control (OSD), Pixel Pitch 0.297mm x 0.297mm, Number of pixels: 1024×768, 16 million color, Brightness: 250cd/m², Contrast 700:1, response time 8ms, Power AC 100V ~ 240V

- Analog Input with D-sub, BNC, S-Video
- Built-in 3D Comb filter & 3D Noise Filter
- NTSC/PAL Auto Scan
- 140-Degree Viewing Angles
- Y/C and Composite Video Input
- Looping Device
- Resolution Up to 1280×1024 XVGA and 1000:1 Contrast Ratio
- Built-in Audio
- Built-in Multi-Language OSD Menu

Specifications	
Model Number	HCD-15AH
Panel Type	15" TFT color LCD
Built in 3D Comb Filter	Yes
Built in 3D Noise Filter	Yes
Screen Size mm	381 diagonal
Viewable size mm	304.1Hx228.1V
Dot Pitch mm	0.297 x 0.297
Viewing Angle L/R/T/B	70/70/65/60

Specifications	
Contrast Ratio	700:1
Brightness	250 cd/m2
Resolution	1024×768
Display Color	16.2M+
Response Time	8ms
Power Input	100~240VA
Power Consumption	30W
Dimension WxHxD (inch)	13.12" x 13.1" x 6.63"
Weight (lbs)	12.2 lbs
Wall Mount	VESA 100×100 STD
Input Signal PC	1 VGA
Input Signal Video (NTSC/PAL)	1 BNC In/Out, 1 S-Video In/Out
Audio Input	1 x RCA jack (L/R)
Audio Output	1 x RCA jack (L/R)
Plug & Play	DDC2B
Power Management	VESA DPMS Standard
Accessory	User's Manual, VGA Cable & Power Cable
Regulation	UL, FCC, RoHS