



HCD-17AH



FEATURES

17-inch Advanced Security Surveillance TFT LCD Monitor with 3D Comb filter, 3D noise filter, 1 Composite Video in/out, 1 S-Video in/out, VGA in, Audio in/out, View angle: 80/80/80/80 (L/R/T/B), On-Screen Display Control (OSD), Pixel Pitch 0.264mm x 0.264mm, Number of pixels: 1280×1024, 16 million color, Brightness: 250cd/m², Contrast 800:1, response time 5ms, Power AC 100V ~ 240V

- Analog Input with D-sub, BNC, S-Video
- Built-in 3D Comb filter & 3D Noise Filter
- NTSC/PAL Auto Scan
- 140-Degree Viewing Angles
- Y/C and Composite Video Input
- Looping Device
- Resolution Up to 1280×1024 XVGA and 1000:1 Contrast Ratio
- Built-in Audio
- Built-in Multi-Language OSD Menu

Specifications	
Model Number	HCD-17AH
Panel Type	17" TFT color LCD
Built in 3D Comb Filter	Yes
Built in 3D Noise Filter	Yes
Screen Size mm	431 diagonal
Viewable size mm	337.9Hx270.3V
Dot Pitch mm	0.264 x 0.264
Viewing Angle L/R/T/B	80/80/80/80

Specifications	
Contrast Ratio	800:1
Brightness	250 cd/m2
Resolution	1280×1024
Display Color	16.2M+
Response Time	5ms
Power Input	100~240VA
Power Consumption	40W
Dimension WxHxD (inch)	13.13" x 13.02" x 6.6"
Weight (lbs)	13.3 lbs
Wall Mount	VESA 100×100 STD
Input Signal PC	1 VGA
Input Signal Video (NTSC/PAL)	1 BNC In/Out, 1 S-Video In/Out
Audio Input	1 x RCA jack (L/R)
Audio Output	1 x RCA jack (L/R)
Plug & Play	DDC2B
Power Management	VESA DPMS Standard
Accessory	User's Manual, VGA Cable & Power Cable
Regulation	UL, FCC, RoHS