



HCD-17EH



FEATURES

17-inch Entry Level Security Surveillance TFT LCD Monitor Composite Video in/ out, S-Video, VGA, Audio, View angle: 70/70/70/70 (L/R/T/B), On-Screen Display Control (OSD), Pixel Pitch 0.264mm x 0.264mm, Number of pixels: 1280×1024, 16 million color, Brightness: 300cd/m2, response time 12ms, Power AC 100V ~ 240V

- VGA PC Input w/ BNC In/Out & RCA In
- Built-in 2D Noise Filter & 2D Comb Filter
- NTSC/PAL Auto Scan
- 140-Degree Viewing Angles
- Y/C and Composite Video Input
- Looping Device
- Resolution Up to 1280×1024 XVGA and 700:1 Contrast ratio
- Built-in Audio
- Built-in Multi-Language OSD Menu

Specifications	
Model Number	HCD-15EH
Panel Type	17" TFT color LCD
Built in 2D Comb Filter	Yes
Built in 2D Noise Filter	Yes
Screen Size mm	431 diagonal
Viewable ize mm	337.9Hx270.3V
Dot Pitch mm	0.264 x 0.264
Viewing Angle L/R/T/B	70/70/70/70

Specifications	
Contrast Ratio	500:1
Brightness	300 cd/ m2
Resolution	1280×1024
Display Color	16.2M
Response Time	12ms
Power Input	100~240VA
Power Consumption	40W
Dimension WxHxD (inch)	15.74 x 15.35 x 7.08
Weight (lbs)	8.3
Wall Mount	VESA STD
Input Signal PC	1 VGA
Input Signal Video	1 BNC In/Out, 1 S-Video In, 1 RCA Video In
Audio Input	1 x RCA jack (L/R)
Audio Output	2W x 2 (L/R)
Plug & Play	DDC2B
Power Management	User's manual, power code, audio cable, DVI to D-SUB cable
Accessory	UL, CSA, TUV/GS, CE, VCCI, FCC (DOC), BSMI
Regulation	