HCD-185AHD



FEATURES

18.5 inch Advanced Security Surveillance Monitor with 2D-deinterlace, 2D Noise Reduction. HDMI, VGA, BNC and BNC loop out.

- LED Backlight Panel
- Video supports 2D-deinterface, 2D Noise Reduction, 2D Comb Filter
- Overscan / Underscan
- HDMI 1.4 Compliant receiver, HDCP Key
- Fast switching time, Key lock, Running hours, Backlight control adjusts
- Panel Anti Burn-in, ErP, Green Mode

Specifications	
Model Number	HCD-185AHD
Panel Type	18.5″ LED panel (LCM), A Grade
Viewable Size	409.8X230.4
Pixel Pitch	0.3X0.3
Screen Size mm	470.1 diagonal
PC Standard	VESA Timing
PC connector	VGA 15pins D-SUB
Input Signal Video (NTSC/PAL)	BNC input with loop through output (Passive through type, Level 1.0Vp-p/ 75 ohm)
Multi Media Port	HDMI with HDCP
Viewing Angle L/R/T/B (CR≥10)	85/85/80/80
Contrast Ratio	≥ 1000:1
Brightness	180 cd/m²

Specifications	
Resolution	1366×768
Display Color	16.7M (6 bit with Hi-FRC)
Response Time	≤ 5ms
Power Input	AC 100 ~ 240VAC 60/ 50Hz
Power Consumption	16W
Dimension WxHxD (inch)	496x114x377mm(19.5″ x 4.5″ x 15″)
Weight (lbs)	8 lbs
Wall Mount	VESA 100x100mm STD
Audio Input	1 stereo phone jack; input level: 1.0Vp-p / 1 KHZ
Audio Output	1 stereo phone jack; Loop through output, internal speaker 1Wx2
Plug & Play	EDID
Power Management	VESA DPMS Compatible
Accessory	User’s Manual, VGA Cable & Power Cable, Stereo Audio Cable
User”s control	Power ON/OFF, MENU, +, -, DOWN, UP, Source
Regulation	UL, FCC, RoHS