



# HCD-19AH



## FEATURES

19-inch Advanced Security Surveillance TFT LCD Monitor with 3D Comb filter, 3D noise filter, 2 Composite Video in/out, 1 S-Video in/out, VGA in, DVI in, Component in, Audio in/out, View angle: 85/85/80/80 (L/R/T/B), On-Screen Display Control (OSD), Pixel Pitch 0.294mm x 0.294mm, Number of pixels: 1280×1024, 16 million color, Brightness: 250cd/m<sup>2</sup>, Contrast 1000:1, response time 5ms, Power AC 100V ~ 240V

- Analog Input with D-sub, BNC, S-Video
- Built-in 3D Comb filter & 3D Noise Filter
- NTSC/PAL Auto Scan
- 140-Degree Viewing Angles
- Y/C and Composite Video Input
- Looping Device
- Resolution Up to 1280×1024 XVGA and 1000:1 Contrast Ratio
- Built-in Audio
- Built-in Multi-Language OSD Menu

Specifications	
Model Number	HCD-19AH
Panel Type	19" TFT color LCD
Built in 3D Comb Filter	Yes
Built in 3D Noise Filter	Yes
Screen Size mm	482 diagonal
Viewable size mm	376.3Hx301.1V
Dot Pitch mm	0.294×0.294
Viewing Angle L/R/T/B	85/85/80/80

<b>Specifications</b>	
Contrast Ratio	1000:1
Brightness	250 cd/m <sup>2</sup>
Resolution	1280×1024
Display Color	16.2M+
Response Time	5ms
Power Input	100~240VA
Power Consumption	50W
Dimension WxHxD (inch)	14.6" x 14.5" x 6.6"
Weight (lbs)	15.6 lbs
Wall Mount	VESA 100×100 STD
Input Signal PC	1 VGA, 1 DVI, 1 Component
Input Signal Video (NTSC/PAL)	2 BNC In/Out, 1 S-Video In/Out
Audio Input	1 x RCA jack (L/R)
Audio Output	1 x RCA jack (L/R)
Plug & Play	DDC2B
Power Management	VESA DPMS Standard
Accessory	User's Manual, VGA Cable & Power Cable
Regulation	UL, FCC, RoHS