



# HCD-19MAH



## FEATURES

19-inch Security Surveillance Metal Case LCD Monitor with 3D Filter, 2 Composite Video in/out, S-Video, VGA, DVI, Audio in/out, View angle: 75/75/70/60 (L/R/T/B), On-Screen Display Control (OSD), Pixel Pitch 0.294mm x 0.294mm, Number of pixels: 1280×1024, 16.7 million color, Brightness: 300cd/m2, response time 12ms, Power AC 100V ~ 240V

- Digital/Analog Input with DVI-I and D-sub
- Built-in 3D Filter
- NTSC/PAL Auto Scan
- 140-Degree Viewing Angles
- Y/C and Composite Video Input
- Looping Device
- Resolution Up to 1366×768 and 2500:1 Contrast Ratio (HCD-26MAH)
- Built-in Audio
- Built-in Multi-Language OSD Menu

Specifications	
Model Number	HCD-19MAH
Panel Type	19" TFT color LCD
Built in Filter Type	3D
Viewable ize mm	376.3Hx301.1V
Dot Pitch mm	0.294×0.294
Viewing Angle L/R/T/B	75/75/70/60
Contrast Ratio	500:1
Brightness	300 cd/m2

Specifications	
Resolution	1280×1024
Display Color	16.2M+
Response Time	12ms
Power Input	100~240VA
Power Consumption	60W (Max)
Dimension WxHxD mm	16.53×14.72×3.1
Weight (lbs)	18.9
Wall Mount	VESA STD
Input Signal PC	Fh: 31.5k~80Khz, Fv: 50~75Hz; Connector: DVI-1 (Digital + 2 Analog)
Input Signal	NTSC/ PAL dual Scan composite video Connector: Level: 1.0Vp-p/ 75 ohm
Input Connectors	2 BNC In/Out, 1 VGA, 1 DVI, 1 S-Video In/Out
Audio	2 x RCA jack (L/R) In/Out
Plug & Play	DDC2B
Power Management	User's manual, power code, audio cable, DVI to D-SUB cable
Accessory	FCC, CE, UL, TCO
Regulation	