



# HCD-22AH



## FEATURES

22-inch Advanced Security Surveillance TFT LCD Monitor, Composite Video in/out, VGA in, View angle: 85/85/80/80 (L/R/T/B), On-Screen Display Control (OSD), Pixel Pitch 0.282mm x 0.282mm, Number of pixels: 1680×1050, 16 million color, Brightness: 300cd/m<sup>2</sup>, Contrast 700:1, response time 8ms, Power AC 100V ~ 240V

- Composite Video in/out
- View angle: 85/85/80/80 (L/R/T/B), On-Screen Display Control (OSD), Pixel Pitch 0.282mm x 0.282mm
- Number of pixels: 1680×1050, 16 million color, Brightness: 300cd/m<sup>2</sup>, Contrast 700:1, response time 8ms
- Power AC 100V ~ 240V

Specifications	
Model Number	HCD-22AH
Display Type	22" 16:10 Active Matrix TFT LCD Panel
Pixel Pitch	0.282(H) x .282(V) mm
Resolution	1680 x 1050
Display Area (WxH)	73.76mm x 296.1 mm (18.65 x 11.67 in)
Contrast Ratio	700:1
Viewing Angle	85/85/80/80 (L/R/T/B)
H Frequency	31-65 kHz
V Frequency	60-75 Hz
Display Colors	6.7M
Brightness	300 cd/m <sup>2</sup>

<b>Specifications</b>	
Response Time	8ms
Input Signal PC	1 VGA
Input Signal (NTSC/PAL)	1 x BNC In, 1x BNC Out
Display Mode	VGA/SVGA/XGA/WSXGA
Operating Humidity	20~80%
Operating Temperature	0°C~40°C (32°F~113°F)
Storage Humidity	20~80%
Storage Temperature	-20°C~+60°C (-4°F~+140°F)
Power	AC 100-240V, 50/60 Hz
Regulation	Schedule, Event (Pre/Post), Manual (Emergency)