



HCD-26MAH



FEATURES

26-inch Security Surveillance Metal Case LCD Monitor with 3D Filter, 2 Composite Video in/out, VGA, DVI, View angle: 88/88/88/88 (L/R/T/B), On-Screen Display Control (OSD), Pixel Pitch 0.4215mm x 0.4215mm, Number of pixels: 1366×768, 16.7 million color, Brightness: 450cd/m², response time 8ms, Power AC 100V ~ 240V

- Digital/Analog Input with DVI-I and D-sub
- Built-in 3D Filter
- NTSC/PAL Auto Scan
- 140-Degree Viewing Angles
- Y/C and Composite Video Input
- Looping Device
- Resolution Up to 1366×768 and 2500:1 Contrast Ratio (HCD-26MAH)
- Built-in Audio
- Built-in Multi-Language OSD Menu

Specifications	
Model Number	HCD-26MAH
Panel Type	26" TFT color LCD
Built in Filter Type	3D
Viewable size mm	575.8Hx323.7V
Dot Pitch mm	0.294×0.294
Viewing Angle L/R/T/B	88/88/88/88
Contrast Ratio	2500:1
Brightness	450 cd/m ²

Specifications	
Resolution	1366×768
Display Color	16.2M+
Response Time	8ms
Power Input	100~240VA
Power Consumption	140W (Max)
Dimension WxHxD mm	25.6x18x4.03
Weight (lbs)	30.8
Wall Mount	VESA STD
Input Signal PC	Fh: 31.5k~80Khz, Fv: 50~75Hz: Connector: DVI-1 (Digital + 2 Analog)
Input Signal	NTSC/ PAL dual Scan composite video Connector: Level: 1.0Vp-p/ 75 ohm
Input Connectors	2 BNC In/Out, 1 VGA, 1 DVI, 1 S-Video
Audio	N/A
Plug & Play	DDC2B
Power Management	User's manual, power code, audio cable, DVI to D-SUB cable
Accessory	FCC, CE, UL, TCO
Regulation	