

HCR-T9608



FEATURES

8 Ch 960H Real Time Digital Video Recorder

- H.264 Compression (High Profile)
- 8ch 960H Video Input
- 960H Real Time on Live View
- RS-485 over Coax (PTZ, Camera Menu Control)
- Real Time Recording & Playback Max. 30(25)fps per Channel
- HDMI & VGA Output - Full HD (Max. 1920 x 1080)
- Picture Quality : Utmost Graphic, Respectively Comparing Its Picture Size
- Mobile Viewer : iPad / iPhone / Android
- Dual Stream : Optimize Network Transfer Speed
- POS text insertion (Patent Pending) : Displaying & Recording Transaction Data from POS
- User Friendly GUI : Flexible, Easy and Convenient
- Advanced CMS Software : Convenient and Versatile Software
- S.M.A.R.T : Self Monitoring Analysis and Reporting Technology

Specifications	
Model	HCR-T9608
Compression	H.264 (High Profile)
Operating System	Embedded Linux
OS Firmware	Linux OS in Flash Memory
Signal Format	NTSC or PAL (Auto / Manual)
Memory	512MB DDR3 Memory
Video Input	8 (BNC)
Video Output	1 BNC, 1 VGA, 1 HDMI

Specifications	
(Analog) Spot Out	1
Recording Rate	240 (NTSC) / 200 (PAL)
Audio Input / Output	1 Input / 1 Output
Alarm Input / Output	2 Input / 1 (TTL)
USB 2.0	2 x USB (1 x Front Panel, 1 x Rear Panel)
Ethernet	10 / 100 / 1000 Mbps Ethernet (RJ-45)
User Interface (GUI / Control Device)	Keypad, Mouse, PTZ Control, Remote Controller
Archive File Format	EXE (Video Clip)/ AVI (Video Clip) / JPEG (Still Image)
NTP Server	Yes
GMT Time Zone	Yes
Auto DST	Yes
Recording Qualities	Super / High / Standard / Low
Recording Modes	Continuous / Alarm / Motion / Emergency
Motion Detection	Yes (22 x 15)
Playback Control	x1, x2, x4, x8, x16, x32, x64, Extreme
RS-485 Control	RS-485/422 Terminal Block, RS-485 through BNC
Text Insertion (POS)	4
Multi Language	Arabic / Chinese (Simplified) / Chinese (Traditional) / Croatian / Czech / Danish / English / French / German / Italian / Japanese / Korean / Persian / Polish / Portuguese / Russian / Spanish / Thai / Turkish
Central Monitoring Station	CMS Pro (Windows) / iCMS (MAC) / xCMS (Linux) / Web Client Pro
Mobile Viewer	iPad / iPhone / Android
Primary Storage	2 x SATA HDD (Up to 6 TB)
Clip Copy Storage	USB Memory Stick
Dimension(WxHxD)	CK1204 / 1208 : 290 mm x 50 mm x 274 mm / 11.42 inch x 1.97 inch x 10.79 inch CK1316 : 290 mm x 50 mm x 329 mm / 11.42 inch x 1.97 inch x 12.95 inch
Operating Temperature	5°C~40°C / 41°F~104°F
Operating Humidity	0% ~ 90%
Power Adapter	12V, 3.33A (40W)
Power Consumption	Max. 25W in Normal Operation