



HDB302-VP



FEATURES

IP Video Intercom Vandal-Resistant Door Station

- IK 9 and IP 66
- Self-Adaptive IR Supplement with Max. 15ft IR distance
- ISAPI and ONVIF supported
- Motion detection
- PoE and 12VDC
- Vandal-proof

Specifications	
Model Number	HDB302-VP
Processor	High-Performance Embedded SOC processor
Operation System	Embedded Linux Operation System
Image Sensor	2MP HD Camera
Lens	Pinhole, 3.47mm, F2.5
Field of View	88° Horizontal, 45° Vertical
Video Compression	H.264
Resolution	1920 x 1080
Frame Rate	30fps @ 1920 x 1080
Video compression	H.264 / MJPEG / H.264+
Dual stream	Yes
Video Bit Rate	32 Kbps - 4096 Kpbs
Wide Dynamic Range	DWDR, Auto-switch, Day/on, Night/off

Specifications	
Image settings	Color, Brightness, Contrast, Sharpness, Saturation, Video Standard, OSD Display
Audio Streaming	Two-Way, Full Duplex
Audio Input	Built-in Omnidirectional Microphone
Audio Output	Built-in Loudspeaker
Audio Compression Standard	G.711 U
Audio Compression rate	64 Kbps
Audio quality	Noise Suppression and Echo Cancellation
Light Supplement mode	IR Supplement, IR Distance: 5 Meters
Wavelength	940nm
I/O Input	1
I/O Output	1 Relay
Event	Motion Detection, Picture Capturing, Call Button Pressing
Impact Protection	IK9
Ingress Protection	IP66
Power Supply	PoE, 12VDC
Power Consumption	Max. 12W
Working Temperature	-30°C to 50°C (-22°F to 122°F)
Dimensions	6.37" x 2.92" x 2.09"
Weight	1.7 lbs