



HDR503-8



FEATURES

8-ch H.264/MPEG4 HD video/Audio Decoder

- H.264 and MPEG4 video stream supported
- 4-ch Decoder
- Up to 5 Megapixels resolution decoding
- HDMI and VGA output at up to 1920×1080P resolution
- SADP(IP Finder),UDP, RTP and NTP protocols
- Video display on TV wall
- Active and passive decoding modes
- 32 users with multi-user level management

Specifications	
Model Number	HDR503-8
VGA output	8-ch
VGA output resolution	1920×1080@60 / 50HZ, 1600 x 1200 @60Hz, 1280 x 1024@60Hz, 1280 x720 @ 50/60Hz, 1024 x 768@60Hz
HDMI output	8-ch
HDMI output resolution	1920×1080@60 / 50HZ, 1600 x 1200 @60Hz, 1280 x 1024@60Hz, 1280 x720 @ 50/60Hz, 1024 x 768@60Hz
CVBS output	none
Audio output	8-ch, RCA connector
IP video input	H.264 / MPEG4
Decoding Capability	8-ch at 5MP / 1080P; 16-ch at 720P; 32-ch at 4 CIF resolution
Multi-division Display	1/4/9/16

Specifications	
Audio compression	OggVorbis
Two-way audio input in	2-ch, 3.5mm connector (2.0 Vp-p, 1kΩ)
Network Interface	10/100/1000Mbps self-adaptive Ethernet interface
Serial Intreface	1 RS-232 (DB9), 1 RS-485
Alarm In	4
Aarlm Out	4
Power Supply	220 VAC
Power Consumption	Max. 70W
Working temperature	-10°C ~ +58°C
Working Humidity	10% ~ 90%
Chassis	19-inch rack-mouted 1.5U chassis
Dimensions (W x D x H)	445 x 390 x 70mm
Weight(without HDD)	5.2kg