

HEAR504-8



FEATURES

8-ch H.264/MPEG4/MPEG2/MJPEG Video Encoder

[dt_quote type="pullquote" layout="left" font_size="big" animation="none" size="1"]**This model has been replaced by the [HEAR526-8](#)**[/dt_quote]

- H.264/MPEG4/MPEG2/MJPEG encoding standards supported
- Support encoding video at up to 4CIF resolution
- One independent PoE network interfaces
- Connectable with network HDD in NAS, IPSAN mode
- Support multiple network protocols, including IPv4/v6, HTTP, HTTPS, QoS layer3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3, OnVIF, PSIA, SOCKSv4/v5, etc.;
- Multiple PTZ protocols

| Specifications | |
|----------------------|----------------------------------|
| Model Number | HEAR504-08 |
| Video Compression | H.264 / MPEG4 / MPEG2 / MJPEG |
| Video input | 8-ch, BNC (1.0Vp-p, 75Ω) |
| Audio Compression | G.711u |
| Audio input | 4-ch RCA (2.0 Vp-p, 1 KΩ) |
| Two-way audio input | 1-ch |
| Audio output | 1-ch RCA (Linear, 1 KΩ) |
| Recording resolution | 1080P/720P/WD1/4CIF/VGA/CIF |
| Frame rate | 1/16 fps to real time frame rate |
| Video bit rate | 32 Kbps ~ 10 Mbps |
| Audio bit rate | 64 Kbps |

| Specifications | |
|------------------------|--|
| Dual-stream | Support |
| Stream type | Video, Video & Audio |
| Type | NAS, iSCSI, IPSAN |
| Capacity | 2 internal SATA up to 6TB ea. |
| Network interface | 1 RJ-45 10M/100 Mbps adaptive Ethernet interface (PoE) |
| Protocols | IPv4/v6, HTTP, HTTPS, QoS layer3 DiffServ, FTP, SMTP, Bonjour, UPnP, SNMPv1/v2c/v3(MIB-11), DNS, DynDNS, hkDDNS, NTP, RTSP, RTP/RTCP, TCP, UDP, IGMP, ICMP, DHCP, ARP, SOCKSv4/v5, PSIA, OnVIF, Hik CGI, netFilter |
| Serial interface | 1 half-duplex RS-485 interface |
| Alarm in | 8 |
| Alarm out | 4 |
| Power supply | 12 VDC |
| Consumption | ≤ 30W |
| Working temperature | -10 °C ~ +55 °C |
| Working humidity | 10% ~ 90% |
| Dimensions (W x D X H) | 14.96" × 11.42" × 1.89" |
| Weight | 4.41 Lbs |