



HHRA03-16



FEATURES

16 Ch Analog + Up to 32 ch IP Hybrid DVR

- 80 Mbps Bit Rate Input Max for IP Cameras
- H.264 video compression
- WD1 (960 x 480) resolution real-time recording
- Third-party network cameras supported
- Up to 5 Megapixels resolution recording(HNC105-VB & HNC105-ZD only)
- HDMI and VGA output at up to 1920×1080 P resolution
- 16 ch synchronous playback
- Dual Gigabit network interfaces
- ONVIF compliant

Specifications	
Model Number	HHRA03-16
Video Compression	H.264
IP Video Input	UP to 32 ch (80Mbps Bit Rate Input max)
Video Output	1 HDMI, 1 VGA, 1 BNC
Analog Video Input	16
Video Loop Out	16
Audio Input/output	4/2
Two-way Audio	1/1
Real-time recording resolution	30fps @ Up to 5 Megapixels(HNC105-VB & HNC105-ZD)
HDMI Output Resolution	Up to 1080P/60Hz
VGA Output Resolution	UP to 1080P/60Hz

Specifications	
Synchronous Playback	16 ch
Alarm Input/ Output	16/4
Network Interface	2, RJ45 10M/100M/1000M adaptive Ethernet Interface
PoE Network Interfaces/Built-in switch	N/A
HDD Interface	8 SATA interfaces(up to 6TB each)
eSATA	1 eSATA
USB interface	3, USB2.0
Chassis	19-inch rack-mounted 2U
Power Supply	100~240VAC
Weight	17.64 lbs (without hard disk)