HKD8002-VM



FEATURES

Video Intercom Metal Door Station

- Video Intercom Function
- Access Control Function
- Card Readers Supported
- HD Video surveillance with high performance CMOS
- 12VDC

Specifications	
Model Number	HKD8002-VM
Processor	High-Performance Embedded SOC processor
Operation System	Embedded Linux Operation System
Camera	CMOS Low Illumination 1.3MP HD Colorful Camera
Video Compression	H.264
Resolution	1280 x 720
Frame rate	30fps @ 1280 x 720
Display Screen	3.5-inch Colorful TFT LCD
Display resolution	480 x 320
Operation Method	Physical Keypad
Audio Input	Built-in Omnidirectional Microphone
Audio Out	Built-in Loudspeaker
Audio Compression Rate	64Kbps
Internal Card Reader	Built-in IC card reader
External Card Reader	Wiegand 26, Wiegand 34, or RS-485 IC Reader

Specifications	
Door Magnetic Detection	Detects Door Magnetic Status
Light Supplement mode	Visible Light Supplement
Ethernet	10 / 100 / 1000 Mbps Self-Adaptive Ethernet
Alarm Input	Door Magnetic Alarm, Tampering Alarm
Network Interface	1 RJ-45 10/100/1000 Mbps Self-Adaptive Ethernet Interface
RS-485	1 RS-485 Half-Duplex Port
I/O Input	8
I/O Output	4
Wiegand	1 Wiegand Port for Accessing Wiegand IC Card Reader
USB	1 USB 2.0, Supporting U-Disk
Material	Alluminum Alloy
Ingress Protection	IP65
Power Supply	12VDC
Power Consumption	Max. 15W
Working Temperature	-40°C to 60°C (-40°F to 140°F)
Dimensions	16.5″ x 5.7″ x 2.4″
Certification	FCC, IC, CE, C-TICK, ROHS, REACH, WEEE