



HLSM-283



FEATURES

2.8" Portable Day/light viewing Monitor.

- Active Area 57.6(mm)(H) x 43.2mm(V)
- Resolution: 320 x 240
- Contrast Ratio: 10,000 : 1, Brightness: 200cd/m²
- Video System: NTSC & PAL 1 BNC input & 1 BNC connector for CVBS loop-through output

| Specifications | |
|----------------------|---|
| Model Number | HLSM-283 (2.83" Portable Day/light Viewing Monitor) |
| Display Screen | 2.83" |
| Active Area (mm) | 57.6mm (H) x 43.2mm (V) |
| Dot Pitch | 0.18mm x 0.06mm |
| Contrast Ratio | 10,000:1 |
| Brightness | 200 cd/m ² |
| Display Colors | 262k |
| Resolution | 320 x 240 |
| Video Output | 1 BNC connector for CVBS loop-through output |
| Video Input | Composite video, connector: 1 BNC Level: 1.9Vp-p / 75 Ω |
| OSD | Contrast, battery indicator & information |
| System Compatibility | NTSC: 1570Hz +/-500Hz / 60Hz, PAL: 15625Hz +/- 500Hz / 50 Hz |
| Charging Time | 3 Hours Average |
| Working Time | Continuously display time: 3 hours average Standby time: around 6 hours |

| Specifications | |
|---------------------|---|
| Additional Benefits | 4:3 Aspect Ratio |
| Power Supply | Dconsumption: < 2w; Battery: 1200mah Li-ion battery (Embedded inside the monitor) Input Voltage: 3.7Vdc (INterneal Li-ion rechargeable battery) Charger: Input: 100 -240 Vac, output: 5Vdc |
| Note | The charging and working period will vary correspondence with environment temperture specifications subjezt to change without notice |