



HNC-6825G0-C-IVS



FEATURES

2MP Dual-Lens People Counting Network Camera

- Up to 2 megapixel (1920 × 1080) resolution
- Water and dust resistant (IP67)
- Efficient H.265+ compression technology

Specifications	
Model	HNC-6825G0/C-IVS
Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	Color: 0.005 Lux @ (F1.2, AGC ON), 0.0176 Lux @ (F2.25, AGC ON) B/W: 0.001 Lux @ (F1.2, AGC ON), 0.0035 Lux @ (F2.2.5, AGC ON)
Shutter Speed	1/25 s - 1/100,000 s
Lens	2mm
Lens Mount	M12
Day & Night	IR cut filter with auto switch
Digital Noise Reduction	3D DNR
Wide Dynamic Range	Digital WDR
Video Compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG
Video Bit Rate	32 Kbps - 16 Mbps
Dual Stream	Yes
Max. Resolution	2MP CMOS,(1920 × 1080)

Specifications	
Frame Rate	50Hz: 25fps (1920 × 1080, 1280 × 720) 60Hz: 30fps (1920 × 1080, 1280 × 720)
Image Settings	Saturation, brightness, contrast, sharpness are adjustable by client software or web browser
Backlight compensation	Yes, zone optional
ROI	Supported, max 1 ROI
Network Storage	NAS
Audio	1 built-in mics
Alarm Trigger	Motion detection, Dynamic analysis, Tampering alarm
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
Security	User Authentication, Watermark
Standard	ONVIF, PSIA, ISAPI
Communication Interface	1 RJ45 10M/100M Ethernet interface
Reset Button	Yes
Operating Conditions	-30 °C to +45 °C (-22 °F to +113 °F). Humidity 95% or less (non-condensing)
Power Supply	12 VDC±20%, 12 VDC
Power Consumption	Max. 8.3 W
Ingress Protection level	IP67
IR Range	up to 100ft.
Dimensions	With : 168 mm × 61 mm × 41 mm (6.6" × 2.4" × 1.6")
Weight	Approx. 435 g (1 lb.)
Electrical Box	TBA