



HNC301-VB



FEATURES

1.3MP VF IR Bullet Network Camera

- Up to 1.3 megapixel (1280 x 960) resolution
- HD real-time video
- Vari-focal lens
- IR LES (up to 30m)
- DWDR & 3D DNR & BLC
- IP66
- Support onboard storage (up to 64GB)

Specifications	
Model Number	HNC301-VB
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.014 lux @ F1.4 0 lux with IR
Shutter time	1/30s ~ 1/100, 000s
Lens	2.8 - 12 mm @ F1.4, Angle of view: 80°-28.7°. Auto IRIS
Day & night	ICR
Digital noise reduction	3D DNR
Wide dynamic range	Digital WDR
Backlight compensation	Yes, zone configurable
Video compression	H.264 / MJPEG
Bit rate	32 Kbps ~ 16 Mbps
Max, image resolution	1280 x 960

Specifications	
Frame rate	60 Hz 30 fps (1280 x 960), 30 fps (1280 x 720)
Image settings	Saturation, brightness, contrast adjustable through client software or web browser
Network storage	NAS
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System Compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark, dual stream
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Onboard storage	Built-in Micro SD/SDHG/SDXG card slot, up to 64 GB
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	DC12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max. 5.5W (Max, 7.5W with ICR on)
Ingress protection level	IP66
IR range	UP to 30m
Dimension	95 x 105 x 258.6 mm (3.74" x 4.13" x 10.18")
Weight	1200g
Electrical Box	HTH-260ZJ