



HNC303-TD



FEATURES

3MP IR Fixed Focal, Vandal-Proof Dome Camera

- This model has been replaced by [HNC324-TD/TDB](#)
- 3 Megapixel (2048 x 1536) Resolution
- Full HD 1080p real-time video
- 3 axis
- 3D DNR & DWDR & BLC
- IP66 Rating
- PoE
- Vandal-proof

Specifications	
Model Number	HNC303-TD
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ F2.0, AGC ON, 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	4mm @ F2.0, angle of view: 75.8° (2.8mm optional)
lens mount	M12
Angle adjustment	Pan: 0° ~ 355°, tilt: 0° ~ 65°, rotation:0° ~ 355°
Digital noise reduction	3D DNR
Wide Dynamic Range	Digital WDR
Day & night	True
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile

Specifications	
Audio	N/A
Dual stream	Yes
On Board Storage	Micro SD up to 128GB
Max. image resolution	3MP CMOS,(2048 x 1536)
Frame rate	60Hz: 20fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
Network storage	NAS
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
Alarm	N/A
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	7W Max
Ratings	IP66 / IK10
IR range	approx 100ft
Dimensions	Ø 4.4" x 3.2"
Weight	500g (1.1 lbs)
Electrical Box	HTH-280ZJ-DM18
Wall Mount	HTH-258ZJ, HTH-272ZJ-110B
Pendant	HTH-271ZJ-110
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ