HNC303-VB



FEATURES

3MP VF IR Bullet, Exterior

- This model has been replaced by HNC324-VBZ
- 3 Megapixel (2048 x 1536) Resolution
- Full HD 1080p real-time video
- Vari-focal lens
- IR LEDs (up to 100ft.)
- True WDR & 3D DNR & BLC
- IP66
- On-board storage (up to 128GB)

Specifications	
Model Number	HNC303-VB
Image Sensor	1/3″ progressive scan CMOS
Min. illumination	0.01 lux @F1.2, 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	2.8 – 12 mm @ F1.4, Angle of view: 105.2°-31.9°. Auto IRIS
Day & night	ICR
Digital noise reduction	3D DNR
WideDynamic Range	True WDR, 120db
Backlight compensation	Yes, zone configurable
Video compression	H.264 / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps

Specifications	
Max. image resolution	3MP CMOS,(2048 x 1536)
Frame rate	60Hz: 15fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Network storage	NAS
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception, storage error
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark, dual stream
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Onboard storage	Built-in Micro SD/SDHG/SDXG card slot, up to 128 GB
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max. 5.5W (7.5W with ICR on)
Ingress protection level	IP66
IR range	Up to 100ft.
Dimensions (mm)	95 x 105 x 258.6mm (3.74″ x 4.13″ x 10.18″)
Wall Mount	W:HTH-260ZJ
Pole,Corner	P:HTH275ZJ,C:HTH276ZJ
Weight	1200g (2.64 lbs)