



HNC304-XB



FEATURES

4MP WDR EXIR Bullet, Exterior

- This model has been replaced by [HNC324-XB](#)
- 4 Megapixel High Resolution
- Full HD 1080p Video Output
- Low Illumination
- 3D DNR & True WDR & BLC
- IP66 Rating
- IR Range: up to 150ft
- True Day / Night

Specifications	
Model Number	HNC304-XB
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/30s ~ 1/100,000s
Lens	4mm @ F2.0 (6mm, 12mm optional) Angle of view: 75.8°
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR
Video compression	H.264 / MJPEG / H.264+
Max. Image Resolution	4MP CMOS,(2688 x 1520)
Frame rate	20fps (2688×1520), 30fps (1920×1080)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser

Specifications	
BLC	Yes, zone configurable
Network storage	NAS
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Interoperability	ONVIF, PSIA, CGI
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 7.5W
Weather proof rating	IP66
IR range	UP to 150ft
Dimension	11.8"x3.4"x3.35"
Weight	700g(1.5lbs)
Electrical Box	HTH-260ZJ
Pole,Corner	P:HTH-275ZJ,C:HTH-276ZJ