



HNC312-PHC



FEATURES

2.0MP Corner Network Camera

- 1920 x 1080 high resolution
- 120dB WDR
- ROI codec

Specifications	
Model Number	HNC312-PHC
Image Sensor	1/2.7" Progressive Scan CMOS
Min. Illumination	0.025 Lux @ (F1.2, AGC ON) 0.022 Lux @ (F2.5, AGC ON)
Shutter Speed	1/3s ~ 1/100,000s
Slow Shutter	Support
Lens	3.7mm, angle of view: 78 °
Lens Mount	Corner
Day & Night	Electronic
Digital Noise Reduction	3D DNR
Wide Dynamic Range	120dB
Video Compression	H.264 / H.264+ / H.265
H.264 Type	Main Profile
Video Bit Rate	32 Kbps - 8 Mbps
Max. Resolution	1920 × 1080
Frame Rate	30fps (1920 × 1080)
ROI	support

Specifications	
Network Storage	NAS
Alarm Trigger	Motion detection, video tampering, IP address conflict, illegal login
Protocols	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv6, Bonjour (SIP optional)
Standard	ONVIF, ISAPI
Communication Interface	1 RJ45 10M/100M Ethernet port
Operating Conditions	-30 °C - 60 °C (-22 °F - 140 °F) Humidity 95% or less (non-condensing)
Power Supply	DC12V ± 10%
Power Consumption	Max. 3W
Dimensions	8 X 8 X 8 in
Weight	(~1.2kg)