



HNC322-CU



FEATURES

2MP IR Cube

- 2MP high resolution
- HD real-time video
- PIR detection
- IR LEDs (up to 30feet)
- DWDR & 3D DNR & BLC
- PoE
- SD/SDHC/SDXC card slot (up to 128GB)
- Wi-Fi enabled (WPS connection)
- Audio enabled (1/1)

Specifications	
Model	HNC322-CU
Image sensor	1/2.7" progressive scan CMOS
Min. illumination	0.01 lux @F1.2, AGC ON, 0 lux with IR
Lens	2.8mm@ F2.0, Angle of view: 114°
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide Dynamic Range	120dB
PIR Range	30ft.
Video compression	H.264 / H.264+ / H.265 / H.265+ / MJPEG
H.264 codec profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Audio	1/1,built in mic, built-in speaker

Specifications	
Audio compression	G722.1/G711ulaw/G711alaw/G726/MP2L2/PCM
Audio bit rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-160Kbps(MP2L2)
Max. Image Resolution	1920 x 1080
Frame rate	30fps (1920 × 1080)
Network storage	NAS
System compatibility	ONVIF, ISAPI
Communication interface	1 RJ45 10M/100M Ethernet interface
Onboard storage	Built-in Micro SD/ SDHC/ SDXC card slot, up to 128 GB
Alarm I/O	1/1
Wi-Fi standard	IEEE 802.11b/g/n
Frequency range	2.412 GHz ~ 2.4835 GHz
Communication bandwidth	Support 20/40 MHz
Protocols	802.11b: DQPSK, DBPSK, CCK 802.11g/n: OFDM/64-QAM, 16-QAM, QPSK, BPSK
Transmission range	50m
Operating conditions	-10°C - 40°C, Humidity 95% or less (non-condensing)
Power supply	DC12V±25% / PoE(802.3af)
Power consumption	Max. 7W
IR range	up to 30 feet
Dimension	4.1" x 2.6" x 1.3"
Weight	400g(0.3lbs)