



# HNC322G2-MB-2



## FEATURES

2MP IR Mini Bullet, Exterior

- Up to 2 megapixel (1920 × 1080) resolution
- 3rd stream with VCA functions off
- High-performance and long service life Infrared LED, Approx. 100ft. IR range
- Focus on human and vehicle targets classification based on deep learning
- PoE (Power over Ethernet)

Specifications	
Model	HNC322G2-MB
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.005Lux @ (F1.6, AGC ON) ,0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens	4mm (2.8mm optional)
Day &Night	IR cut filter with auto switch
Digital Noise Reduction	3D DNR
Wide Dynamic Range	True WDR
Video Compression	H.265/H.264/MJPEG
3rd Stream	Yes(with VCA functions off)
Max. Resolution	2MP (1920 × 1080)
Frame Rate	60Hz: 30fps(1920 × 1080), 30fps (1280 × 960), 30fps (1280 × 720)
Image Settings	Rotate mode, Saturation, Brightness, Contrast adjustable by client software or web browser
Backlight compensation	Yes, zone optional

<b>Specifications</b>	
ROI	Supported, max 1 ROI
Network Storage	NAS
Protocols	TCP/IP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTSP,PPPoE,NTP,SMTP,SNMP,IPv6
Security	User Authentication, Watermark
Standard	ONVIF, ISAPI
Communication Interface	1 RJ45 10M/100M Ethernet interface
Reset Button	Yes
Operating Conditions	-30 °C - 60 °C (-22 °F - 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 V DC $\pm$ 10% , PoE (802.3af)
Power Consumption	Max. 6W
Ingress Protection level	IP67
IR Range	up to 100ft.
Dimensions	Ø2.8" × 6.4"
Weight	500g (1.1 lbs)
Electrical Box	HTH-280ZJ-XS
Pole,Corner	P:HTH-275ZJ,C:HTH-276ZJ